

Wireless Portable Receipt Printer (Smallest size in the world)

MODEL EXPLICATION

PP45Xxxxxxxxx

- B: with battery
- E: Ethernet
- U: Slave (USB)
- 3: RS232
- W2: wireless 2.4G
- W4: wireless 433M
- WB: BT-10M

5:57mm thermal printer



Advanced Features

- ※ Multi-optional wireless communication function: RF2.4G P-tooth, RF433MHz, BT, and IRDA. This wireless printing project is suitable for long/short distance wireless application, rear service, and storage carrying, etc.
- ※ RF2.4G/RF433MHz applies Aclas' patent CSMA communication protocol, which is able to establish many-to-many communication.
- ※ Powered by inbuilt 3.7V Li-battery makes the externality dexterous and no memory effects, which support a longer life than that of 2 pieces dry-battery. With excellent potable function, it can be hung on the waist and integrated to be a mobile sale group (able to print about 300 pieces of receipt) with the Handy Terminal.
- ※ With easy loading paper installation, no worry about paper jam.
- ※ Optional wired communication function: RS232 port/USB port/Ethernet port, which supports graphic printing.
- ※ Support ESC/P command collection, and provide Windows drivers.
- ※ Dustproof and waterproof crust meets the standard of IP54. It is an ideal device for outdoor use.

Application Scope

- ※ POS label printer is suitable for supermarket, restaurant, retailing, etc. to print barcode label, which realizes POS periphery wireless collocation.
- ※ Portable wireless portable receipt printer is suitable for mobile police, mobile meter reading, and administration charging, etc.
- ※ With battery and no-battery two models for choosing. With battery model is the portable one, and no-battery model is the common desktop printer.



work as a mobile printer with handy terminal

Technical Specification

Printing mode	Line thermal printing
Paper width	58mm
Effective printing width	48mm
Printing density	8dots/mm, 384dots/line
Print font	12*24 letters; 24*24 Chinese character
Printing speed	50mm/s
Interface	Standard parallel ports (adapter cable to convert serial ports is needed) or standard RS232 serial ports, USB port, Ethernet port, cash-drawer port.
Wireless	433M, Distance: Max. 100meters 2.4G, Distance: Max. 30meters BT, Distance: Max. 10meters
Power supply	DC 7V/2A
Printer head life	50 kilometers
Size	82*143*74mm(with hangs)



hang in the wall